

# ANNEXURE-X

DEVIATION TEST REPORT OF LAMER-PANGA BLOCK-A (G3)					
SL. NO.	BH No.	BH DEPTH (meter)	READING DEPTH (meter)	AZIMUTH (Degree)	BH INCLINATION ANGLE (Degree)
1	LPA/G3/01	50	8	317.00	44.00
			14	317.00	44.10
			20	317.30	44.00
			26	317.40	44.20
			32	317.80	44.30
			38	317.70	44.40
			44	317.40	44.60
			50	317.80	44.90
2	LPA/G3/02	50	8	317.90	44.70
			14	320.00	45.40
			20	320.70	44.60
			26	320.10	45.00
			32	319.70	44.70
			38	320.70	44.40
			44	321.40	44.40
			50	322.10	44.40
3	LPA/G3/03	35	5	312.40	50.20
			11	312.00	50.30
			17	312.40	50.20
			23	311.30	50.10
			29	311.00	49.80
			35	312.20	49.40
4	LPA/G3/04	35	5	311.40	44.30
			11	311.10	44.90
			17	311.30	44.10
			23	311.60	44.10
			29	311.80	44.20
			35	311.60	44.30
5	LPA/G3/05	60	6	307.70	49.30
			12	307.70	49.40
			18	308.50	49.50
			24	308.10	49.80
			30	307.80	50.00
			36	307.20	50.30
			42	308.40	50.50
			48	307.20	50.50
			54	307.50	50.60
			60	308.40	50.80

6	LPA/G3/06	45	9	312.00	49.00
			15	311.30	49.50
			21	310.10	49.60
			27	311.40	49.50
			33	311.60	49.70
			39	310.20	49.90
			45	311.00	49.70
7	LPA/G3/07	35	5	312.10	45.90
			11	312.20	44.40
			17	311.30	44.60
			23	311.50	44.40
			29	311.30	44.90
			35	312.10	44.80
8	LPA/G3/08	35	5	311.5	46
			11	310.3	44.9
			17	310.6	44.6
			23	310.9	44.8
			29	310.8	44.6
			35	310.4	44.7
9	LPA/G3/09	35	5	313	44.94
			11	310.5	44.94
			17	310.2	45.32
			23	309.8	45.49
			29	310.5	45.03
			35	310.3	45.05
10	LPA/G3/10	115	1	310.2	49.27
			7	310	49.83
			13	308.8	49.09
			19	308.75	50.84
			25	308.6	50.61
			31	308.47	50.59
			37	308.4	50.3
			43	307.8	50.56
			49	307.2	50.94
			55	307.9	50.14
			61	307	50.17
			67	307.4	50.78
			73	307.8	50.54
			79	307.9	50.95
			85	307.8	50.24
			91	307.4	50.94
			97	308.1	50.39

			103	308.9	50.78
			109	308.7	50.16
			115	308.9	50.7
11	LPA/G3/11	77	5	310	55
			11	312.34	54.85
			17	311.5	54.62
			23	311	54.5
			29	310.91	54.41
			35	311.3	54.31
			41	311.1	54.45
			47	312.3	54.23
			53	311.7	54.55
			59	311.9	54.11
			65	310.9	54.22
			71	310.8	54.22
			77	310.7	54.4
12	LPA/G3/12	62	6	307	59.46
			12	309	59.31
			18	310	59.38
			24	313	59.71
			30	312	59.7
			36	311	59.65
			42	311	59.91
			48	313	59.65
			54	310	59.69
			60	311	59.65
			62	312	60.1
13	LPA/G3/13	71	5	310.2	55.5
			11	310	55.04
			17	310	55.5
			23	312.2	55.48
			29	312.8	55.38
			35	312.82	55.35
			41	312.67	55.31
			47	312.15	55.31
			53	311	55.25
			59	310.9	55.17
			65	311.3	54.89
			71	311.1	54.47

14	LPA/G3/14	42	6	310	45
			12	310.54	45
			18	310.15	44.81
			24	311	44.65
			30	310.9	44.87
			36	309.3	44.89
			42	309.1	44.87
15	LPA/G3/15	59	5	313	49
			11	311	49.1
			17	311.2	49.15
			23	310.5	49.6
			29	307	49.6
			35	311.2	49.7
			41	312.3	49.18
			47	310.9	49.13
			53	310.5	49.2
			59	312.2	49.14
16	LPA/G3/16	42	6	310	45.12
			12	310.13	45.22
			18	310.25	45.04
			24	311.89	45.82
			30	310.78	45.65
			36	309.56	45.59
			42	309.57	44.55
17	LPA/G3/17	35	5	311.7	44.85
			11	311.5	44.93
			17	311.6	44.99
			23	312	45.11
			29	312.6	45.14
			35	312.5	45.03